Hidrobath 7.5 AMP





Impellers



- Noryl injection impeller. Brass threaded insert for a better fit with the motor shaft.
- Ultrasonically Welded impellers

Mechanical Seal de 5/8" type 6A

 Mechanical seals are manufactured using 304 stainless steel, designed to avoid leakage and provide greater durab





	Performance Curve Marathon Motor 7.5 Amp Feet of Water/GPM												
_	80.00												
Vate	70.00												_
of C	60.00												
Total Dynamic Head in Ft of Water	50.00												\dashv
Jea	40.00												
mic	30.00												
Ž	20.00												
Total	10.00												_
	-	0	2	10		10	6	0	8	10	1	00	120
								PM					

Product Features

- Economic 7.5 Amp Pump for Bath
- Glass-Filled Polypropylene pump construction.
- NORYL impeller injection, joined by ultrasonic welding equipment
- Compact Design ideal for under bathtub installations
- Includes union nuts for quick & easy installation and maintenance
- Integrated air switch allows pump to operate with an air button (not included)
- Assembled Pumps with a US brand motor (Marathon-Regal Beloit)

Specifications										
PART NUMBER	0111001	AMB	40°C / 104°F							
PHASE	1	INSUL CLASS	F							
HZ	60	PROTECT CODE	3P001							
RPM	3400	TIME RATING	CONT DUTY							
VOLTS	115	THERMALLY PR	OTECTED							
AMP	7.5	AIR SWITCH								
SF	1.0									

